






Antiskid Rubber Sheet**GS5980 Antiskid rubber sheet**

Our antiskid rubber sheets are produced from specifically blended rubber materials with different surface patterns such as strips, dots, holes to supply suitable antiskid property.

Patterns & Normal Dimensions:

GS5981	GS5982	GS5983	GS5984	GS5985	GS5986	GS5987
						
Thin strip	Thick strip	Round dot	Hole	Triangle	Checker	Willow
Thickness: 3~30mm Width: 1200mm	Thickness: 3~30mm Width: 1200mm	Thickness: 3~30mm Width: 1200mm	Thickness: 10mm Width: 914/1830mm	Thickness: 5mm Width: 1000mm	Thickness: 3~6mm Width: 1400mm	Thickness: 3~6mm Width: 1400mm

Specifications:

Style	Color	Density	Tensile strength	Elongation	Hardness	Temperature
GS5981	Black	1.6g/cm ³	≥2.5Mpa	≥200%	65±5	-30°C~+70°C
GS5982	Black	1.6g/cm ³	≥2.5Mpa	≥200%	65±5	-30°C~+70°C
GS5983	Black	1.6g/cm ³	≥2.5Mpa	≥200%	65±5	-30°C~+70°C
GS5984	Black	1.4g/cm ³	≥5.0Mpa	≥300%	70±5	-30°C~+70°C
GS5985	Black	1.5g/cm ³	≥3.0Mpa	≥200%	70±5	-30°C~+70°C
GS5986	Black	1.5g/cm ³	≥3.0Mpa	≥250%	65±5	-30°C~+70°C
GS5987	Black	1.5g/cm ³	≥3.0Mpa	≥250%	65±5	-30°C~+70°C

Normal colors: black, red, blue, grey, etc.

Applications:

Applied for the decorating and paving of tables, grounds and walkways in hotels, gymnasiums, meeting rooms, airports, ports, ships, and vehicles.

Normal Packing:

50kgs/roll, or 10meters/roll.