


**Antistatic Rubber Sheet****GS5915 Antistatic rubber sheet**

The sheets are with strong elasticity, good electrode characteristic, and fine elimination capability for static interference.

**Specifications:**

| Style  | Color       | Density               | Tensile strength | Elongation | Hardness | Temperature |
|--------|-------------|-----------------------|------------------|------------|----------|-------------|
| GS5915 | Black       | 1.55g/cm <sup>3</sup> | ≥3.0Mpa          | ≥150%      | 75±5     | -30°C~+70°C |
| GS5916 | Black/Green | 1.5g/cm <sup>3</sup>  | ≥4.0Mpa          | ≥200%      | 75±5     | -30°C~+70°C |

Other specifications and technical requirements are also available on request.

Normal colors: black, green, one side black and the other green.

**Bulk resistance rate:**

GS5915: 10<sup>6</sup>~10<sup>8</sup>Ω·cm.

GS5916: green side: 10<sup>8</sup>~10<sup>9</sup>Ω·cm; black side: 10<sup>3</sup>~10<sup>5</sup>Ω·cm.

**Applications:**

Applied as paving materials in electronic, textile, printing and dyeing industries where there are high antistatic requirements.

**Normal Dimensions:**

Thickness: 2~20mm;

Width: 500~1200mm;

Length: optional on request.

**Normal Packing:**

50kgs/roll, or 10meters/roll.