

Asbestos Packing with PTFE**PA2000P Asbestos packing with PTFE**

Braided from high quality dusted asbestos yarns and thoroughly impregnated with PTFE. It has good corrosion resistance and long service life.

PA2000PL Asbestos packing with PTFE & lube oil

The packing is similar with PA2000P, but is additionally treated with special lubricant oil, which makes it more flexible. Can be used in high-speed rotating stainless steel shafts or chrome-plated shafts without causing wear.

Applications:

Suitable for both static and dynamic sealing applications, especially for medium-pressure high-speed pumps.

Service Limits:

Style	PA2000P	PA2000PL
Maximum temperature	260°C	260°C
Maximum pressure	100bar	100bar
Shaft speed	10m/s	12m/s
PH range	2~13	2~13
Density	1.2~1.4g/cm ³	1.55~1.75g/cm ³

Forms of Supply:

In coils, e.g. 5kgs or 10kgs per coil;
As packing rings (PR2000P, PR2000PL).

Dimension Table:

For packings with density of 1.3g/cm³

Size (mm)	5	6	8	10	12	14	15	16	18	20	25
Appr. m/kg	30.8	21.4	12.0	7.7	5.3	3.9	3.4	3.0	2.4	1.9	1.2
Appr. g/m	32.5	46.8	83.2	130.0	187.2	254.8	292.5	332.8	421.2	520.0	812.5
Kgs/coil	5									10	

For packings with density of 1.65g/cm³

Size (mm)	5	6	8	10	12	14	15	16	18	20	25
Appr. m/kg	24.2	16.8	9.5	6.1	4.2	3.1	2.7	2.4	1.9	1.5	1.0
Appr. g/m	41.3	59.4	105.6	165.0	237.6	323.4	371.3	422.4	534.6	660.0	1031.3
Kgs/coil	5									10	