

Asbestos Rubber Sheet**GS2200 Asbestos rubber sheet**

Our asbestos rubber sheets are made from selected asbestos fibers, natural rubber, fillers and stainers. A price worthy quality of dependable performance, plus adaptability to many sealing requirements makes this material the most economical choice in the wide range of industrial fields.

Specifications:

Style	GS2220	GS2230	GS2240	GS2245	GS2255
Density	1.8±0.2g/cm ³	1.8±0.2g/cm ³	1.8±0.2g/cm ³	1.8±0.2g/cm ³	1.8±0.2g/cm ³
Tensile strength	≥7Mpa	≥9Mpa	≥13Mpa	≥19Mpa	≥21Mpa
Compressibility	12±5%	12±5%	12±5%	12±5%	12±5%
Recovery	≥30%	≥30%	≥40%	≥45%	≥45%
Stress relaxation	≤50%	≤50%	≤45%	≤40%	≤40%
Maximum temperature	200°C	300°C	400°C	450°C	550°C
Maximum pressure	2.0Mpa	3.0Mpa	5.0Mpa	6.0Mpa	7.5Mpa
Suitable mediums	Water, seawater, steam, alkali, gases, alcohols, salt solutions, etc.				

Available colours: black, purple, red, grey, etc.

Available with inserted wire mesh reinforcement in material of CS (carbon steel), SS304, etc. (style number: GS2200R)

Available with anti-stick coating (style number: GS2200S) or graphite coating (style number: GS2200G) on the surfaces.

Normal Dimensions:

1270 x 1270mm; 3810 x 1270mm; 1000 x 1500mm; 2000 x 1500mm; 4000 x 1500mm;

Thickness: 0.4~5.0mm.

Other dimensions are also available on request.