

Glass Fiber Tape

**TA6120 Glass fiber tape**

Woven from texturized fiberglass yarns. The product offers superior insulating and heat resistant properties, withstanding high temperature in continuous service. It is resistant to many acids and alkalis, and most bleaches and solvents.

TA6127 Glass fiber tape with self-adhesive

With self-adhesive on one side of TA6120 glass fiber tape.

TA6120AL Glass fiber tape with aluminum foil

With a layer of aluminum foil laminated on one side of TA6120 glass fiber tape.

Available to be coated with graphite (style number: TA6120G), silicone rubber (style number: TA6120E), or vermiculite (style number: TA6120V).

Available to be reinforced with stainless steel wire (style number: TA6120R).

Applications:

As an excellent substitute for asbestos tape, glass fiber tape is extensively used for wrapping of steam tracer line, hot pipe protection, exhaust manifold insulation, strip curtains for oven doors, and so on.

Specifications:

Maximum temperature: 450°C~550°C, depending on different types of glass fiber used.

Chemical incompatibilities: Hydrofluoric acid, hot phosphoric, acid and wet hydrogen chloride.

Normal Dimensions:

Thickness: 1.5~5.0mm;

Width: 20~300mm.

Normal Packing:

25m or 30m/roll, then 20kgs/woven bag.