

Neoprene Rubber Sheet**GS5400 Neoprene rubber sheet**

Neoprene (CR) rubber sheet is one of the best all-purpose rubber sheets where resistance to ozone, sunlight, oxidation and many petroleum derivatives are of prime importance. Added advantages include good resistance to water, chemicals, flame, abrasion, flex cracking, etc. It also has good resilience characteristics and tensile strength.

Specifications:

Style	Color	Density	Tensile strength	Elongation	Hardness	Temperature
GS5402*	Black	1.5g/cm ³	≥3.0Mpa	≥200%	65±5	-30°C~+70°C
GS5403	Black	1.3g/cm ³	≥6.0Mpa	≥200%	65±5	-30°C~+70°C
GS5404	Black	1.5g/cm ³	≥9.0Mpa	≥350%	65±5	-30°C~+70°C
GS5411	Red	1.5g/cm ³	≥5.0Mpa	≥300%	60±5	-30°C~+70°C
GS5421	White	1.5g/cm ³	≥5.0Mpa	≥300%	60±5	-30°C~+70°C

* GS5402 is the normal economical neoprene rubber sheet for general application.

Other specifications and technical requirements are also available on request.

Normal color: black.

Applications:

Widely applied to the electronic and thermal aging environments, and where resistance to oil, solvents and fuels is required.

Normal Dimensions:

Thickness: 0.8~80mm for black color; 1.5~12mm for red/white color;

Width: 500~2000mm;

Length: optional on request.

Normal Packing:

50kgs/roll, or 10meters/roll.