


Non-asbestos Latex Sheet Roll**GS3160 Non-asbestos latex sheet roll**

The sheet is made from selected high quality non-asbestos fiber, NBR latex binder and inorganic filling material. The final productions are supplied in big rolls through our unique production line. Length per roll can be customized according to customer requirements. The maximum working temperature of the sheet is 180°C.

GS3160 is **100% asbestos free**.

Applications:

Used as gasket material for explosion engine cylinder gaskets and chemical gaskets. Normally applied in automobile, motorcycle, farm machinery, engineering machinery, etc.

Specifications:

Density		1.0±0.1g/cm ³
Transverse tensile strength		≥10Mpa
Compressibility		20~30%
Recovery		≥30%
In ASTM 3# oil, 150°C, 5h	Thickness increase	≤20%
	Weight increase	≤50%
In ASTM fuel B, 25°C, 5h	Thickness increase	≤20%
	Weight increase	≤40%
In H₂O:(CH₂OH)₂=1:1 100°C, 5h	Thickness increase	≤50%
	Weight increase	≤60%

Normal colour: dark grey.

Other colors are also available based on a minimum order quantity requirement.

Normal Dimensions:

Thickness: 0.4~0.9mm;

Width: 1500mm, 750mm, 500mm;

Length: optional.