


Oil Resistant Asbestos Rubber Sheet**GS2300 Oil resistant asbestos rubber sheet**

Our cost-effective oil resistant asbestos rubber sheets are made from selected asbestos fibers, oil resistant rubber, fillers and stainers. Used in pipelines and apparatus of petrochemical & oil fields.

Specifications:

Style	GS2325	GS2330	GS2340	GS2350
Density	1.8±0.2g/cm ³	1.8±0.2g/cm ³	1.8±0.2g/cm ³	1.8±0.2g/cm ³
Tensile strength	≥11Mpa	≥12Mpa	≥13Mpa	≥15Mpa
Compressibility	12±5%	12±5%	12±5%	12±5%
Recovery	≥40%	≥45%	≥50%	≥50%
Stress relaxation	≤45%	≤45%	≤40%	≤40%
Thickness increase (20# aviation oil)	≤20%	≤18%	≤15%	≤15%
Maximum temperature	250°C	300°C	400°C	500°C
Maximum pressure	2.5Mpa	3.0Mpa	5.0Mpa	7.0Mpa
Suitable mediums	Oils, alkali, mild acid, water, steam, gases, alcohols, etc.			

Available colours: black, green, blue, purple, etc.

Available with inserted wire mesh reinforcement in material of CS (carbon steel), SS304, etc. (style number: GS2300R)

Available with anti-stick coating (style number: GS2300S) or graphite coating (style number: GS2300G) on the surfaces.

Normal Dimensions:

1270 x 1270mm; 3810 x 1270mm; 1000 x 1500mm; 2000 x 1500mm; 4000 x 1500mm;

Thickness: 0.4~5.0mm.

Other dimensions are also available on request.