


Reinforced Asbestos Latex Sheet



GS2100R Reinforced asbestos latex sheet

The product is made from GS2100 asbestos latex sheet reinforced with 0.2~0.25mm tanged steel insertion. The normal steel material used is tin steel or galvanized carbon steel plate.

Applications:

It is extensively used to manufacture various high strength gaskets, cylinder gaskets and motor gaskets. Mainly applied in automobile farming machine, motorcycle and engineering machinery, etc.

Specifications:

Thickness		1.2~2.0mm
Compressibility		18±8%
Recovery		≥35%
Stress relaxation (100°C, 22h)		≤30%
Ignition loss		≤20%
In ASTM 3# oil, 150°C, 5h	Thickness increase	≤20%
	Weight increase	≤20%
In ASTM fuel B, 25°C, 5h	Thickness increase	≤15%
	Weight increase	≤15%

Normal colour: dark grey.

Available with graphite coating (style number: GS2100RG) on the surfaces.

Normal Dimensions:

500 x 1000mm; 500 x 1200mm; 500 x 1500mm; 1000 x 1000mm; 1000 x 1500mm.

Thickness: 1.0~2.0mm.

GS2100R4 Asbestos latex sheet reinforced with tanged steel on both sides

It is a composite sheet made from GS2100 asbestos latex sheet reinforced with 0.2~0.25mm tanged steel on both sides. The normal steel material used is tin steel or galvanized carbon steel plate.

The sheet is extensively used to manufacture various exhaust gaskets for automobile and motorcycle.

Normal Dimensions:

500 x 500mm; 500 x 1000mm;

Thickness: 1.2~2.5mm.