

Reinforced Asbestos Rubber Sheet**GS2200R Reinforced asbestos rubber sheet**

The product is made from asbestos rubber sheet with wire mesh insertion of carbon steel, SS304, etc., offering better capability than the normal asbestos rubber sheets.

Specifications:

Style	GS2220R	GS2230R	GS2240R	GS2245R	GS2255R
Density	1.9±0.2g/cm ³	1.9±0.2g/cm ³	1.9±0.2g/cm ³	1.9±0.2g/cm ³	1.9±0.2g/cm ³
Compressibility	12±5%	12±5%	12±5%	12±5%	12±5%
Recovery	≥30%	≥30%	≥40%	≥45%	≥45%
Stress relaxation	≤50%	≤50%	≤45%	≤40%	≤40%
Maximum temperature	220°C	320°C	420°C	470°C	570°C
Maximum pressure	3.0Mpa	4.0Mpa	5.5Mpa	6.5Mpa	8.0Mpa
Suitable mediums	Water, seawater, steam, alkali, gases, alcohols, salt solutions, etc.				

Available colours: black, purple, red, grey, etc.

Available with anti-stick coating (style number: GS2200RS) or graphite coating (style number: GS2200RG) on the surfaces.

Normal Dimensions:

1270 x 1270mm; 3810 x 1270mm; 1000 x 1500mm; 2000 x 1500mm; 4000 x 1500mm;

Thickness: 0.8~5.0mm.

Other dimensions are also available on request.