


Reinforced Oil Resistant Asbestos Rubber Sheet**GS2300R Reinforced oil resistant asbestos rubber sheet**

The product is made from oil resistant asbestos rubber sheet with wire mesh insertion of carbon steel, SS304, etc., offering better capability than the normal oil resistant asbestos rubber sheets.

Specifications:

Style	GS2325R	GS2330R	GS2340R	GS2350R
Density	1.9±0.2g/cm ³	1.9±0.2g/cm ³	1.9±0.2g/cm ³	1.9±0.2g/cm ³
Compressibility	12±5%	12±5%	12±5%	12±5%
Recovery	≥40%	≥45%	≥50%	≥50%
Stress relaxation	≤45%	≤45%	≤40%	≤40%
Thickness increase (20# aviation oil)	≤20%	≤18%	≤15%	≤15%
Maximum temperature	270°C	320°C	420°C	520°C
Maximum pressure	3.5Mpa	4.0Mpa	5.5Mpa	7.5Mpa
Suitable mediums	Oils, alkali, mild acid, water, steam, gases, alcohols, etc.			

Available colours: black, green, blue, purple, etc.

Available with anti-stick coating (style number: GS2300RS) or graphite coating (style number: GS2300RG) on the surfaces.

Normal Dimensions:

1270 x 1270mm; 3810 x 1270mm; 1000 x 1500mm; 2000 x 1500mm; 4000 x 1500mm;

Thickness: 0.8~5.0mm.

Other dimensions are also available on request.